

Safety Data Sheet

prepared to UN GHS Revision 3

1.1	1. Identification of the Substance/Mixture and the Company/Undertaking							
1.1	Product Identifier	972B (LEAD BASED)	Revision Date: Supercedes Date:	26/03/2018 New SDS				
	Product Name:	Stonkote HT4 Part B (Base) (Drakensberg Green, Reef Green, Manilla, Light Stone, Beechwood)						
1.2	Relevant identified uses of the substance or mixture and uses advised against	Base component of 2 components co	ating - Industrial use.					
1.3	.3 Details of the supplier of the safety data sheet							
	Importer:	Importer						
	Manufacturer:	StonCor Africa (Pty.) Ltd. 8 Cresset Road Midrand Industrial Park, Chloorkop P.O. Box 2205 2001, Johannesburg South Africa						
		Regulatory / Technical Information: +27 11 254 5500						
	Datasheet Produced by:	Maritz, Rory - ehs@stoncor.com						
1.4	Emergency telephone number:	CHEMTREC 1-800-424-9300 (Inside CHEMTREC +1 703 5273887 (Outsid						

2. Hazard Identification

2.1 Classification of the substance or mixture

Acute Toxicity, Inhalation, category 4 Hazardous to the aquatic environment, Chronic, category 2 Carcinogenicity, category 1A Eye Irritation, category 2 Reproductive Toxicity, category 1A Skin Irritation, category 2 Skin Sensitizer, category 1

Label elements 2.2

Symbol(s) of Product



Signal Word

Danger

Named Chemicals on Label

Benzyl alcohol, Lead sulfochromate yellow, Reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight <= 700), phenol, polymer with formaldehyde, glycidyl ether

HAZARD STATEMENTS

Skin Irritation, category 2 Skin Sensitizer, category 1 Eye Irritation, category 2 Acute Toxicity, Inhalation, category 4 Carcinogenicity, category 1A Reproductive Toxicity, category 1A Hazardous to the aquatic environment, Chronic, category 2 PRECAUTION PHRASES	H315 H317 H319 H332 H350-1A H360-1A H411	Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. Harmful if inhaled. May cause cancer. May damage fertility or the unborn child. Toxic to aquatic life with long lasting effects.
	P201	Obtain special instructions before use.
	P202	Do not handle until all safety precautions have been read and understood.
	P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
	P273	Avoid release to the environment.
	P280	Wear protective gloves/protective clothing/eye protection/ face protection.
	P284	Wear respiratory protection.
	P302+352	IF ON SKIN: Wash with plenty of soap and water.
	P304+340	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
	P305+351+338	F IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do so. Continue rinsing.
	P308+313 P308+P313 P333+313 P391	IF exposed or concerned: Get medical advice/attention. IF exposed or concerned: Get medical advice/attention If skin irritation or rash occurs: Get medical advice/attention. Collect spillage.

2.3 Other hazards

No Information

Results of PBT and vPvB assessment:

The product does not meet the criteria for PBT/VPvB in accordance with Annex XIII.

3. Composition/Information On Ingredients

3.2 **Mixtures**

Hazardous Ingredients

CAS-No.	Chemical Name	<u>%</u>
28064-14-4	phenol, polymer with formaldehyde, glycidyl ether	25-50
25068-38-6	Reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight <= 700)	10-25
100-51-6	Benzyl alcohol	2.5-10
13463-67-7	titanium dioxide	2.5-10
1308-38-9	chromic oxide	2.5-10
1344-37-2	Lead sulfochromate yellow	1.0-2.5

Dibutyl phthalate

84-74-2

0.1-1.0

<u>CAS-No.</u>	GHS Symbols	GHS Hazard Statements	M-Factors
28064-14-4	GHS07-GHS09	H315-317-319-411	0
25068-38-6	GHS07-GHS09	H315-317-319-411	0
100-51-6	GHS07	H302-312-319-332	0
13463-67-7			0
1308-38-9	GHS08	H360	0
1344-37-2	GHS08-GHS09	H350-360-373-400-410	0
34-74-2	GHS08-GHS09	H360-400	0
64742-95-6	GHS08-GHS09	H304-411	0

4. First-aid Measures

4.1 **Description of First Aid Measures**

GENERAL NOTES: When symptoms persist or in all cases of doubt seek medical advice.

AFTER INHALATION: Move to fresh air. Consult a physician after significant exposure.

AFTER SKIN CONTACT: Use a mild soap if available. Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. If skin irritation persists, call a physician.

AFTER EYE CONTACT: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses. If eye irritation persists, consult a specialist.

AFTER INGESTION: Gently wipe or rinse the inside of the mouth with water. Give small amounts of water to drink. Do NOT induce vomiting. Never give anything by mouth to an unconscious person.

Self protection of the first aider:

No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

Most important symptoms and effects, both acute and delayed 4.2

Irritating to skin. May cause sensitization by skin contact. Prolonged or repeated exposure increases the risk. Harmful to aquatic organisms.

4.3 Indication of any immediate medical attention and special treatment needed

No information available on clinical testing and medical monitoring. Specific toxicological information on substances, if available, can be found in section 11.

5. Fire-fighting Measures

5.1 **Extinguishing Media:**

Carbon Dioxide, Dry Chemical, Foam

FOR SAFETY REASONS NOT TO BE USED: Alcohol, Alcohol based solutions, any other media not listed above.

5.2 Special hazards arising from the substance or mixture No Information

5.3 Advice for firefighters

In the event of fire, wear self-contained breathing apparatus. High volume water jet. Hazardous decomposition products formed under fire conditions. Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide. Contains epoxy constituents. See information supplied by the manufacturer.

6. Accidental Release Measures

Personal precautions, protective equipment and emergency procedures 6.1

Ensure adequate ventilation. Use personal protective equipment.

6.2 **Environmental precautions**

Do not allow material to contaminate ground water system. Prevent product from entering drains. May cause long-term adverse effects in the aquatic environment.

6.3 Methods and material for containment and cleaning up

Prevent further leakage or spillage if safe to do so. Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13).

6.4 Reference to other sections

Please refer to disposal requirements or country specific disposal requirements for this material. See Section 13 for further information.

7. Handling and Storage

7.1 Precautions for safe handling

INSTRUCTIONS FOR SAFE HANDLING: Use only in area provided with appropriate exhaust ventilation. Wear personal protective equipment.

PROTECTION AND HYGIENE MEASURES: Wash hands before breaks and at the end of workday. When using, do not eat, drink or smoke.

7.2 Conditions for safe storage, including any incompatibilities

CONDITIONS TO AVOID: Extremes of temperature and direct sunlight. **STORAGE CONDITIONS:** Store in original container. Keep locked up or in an area accessible only to qualified or authorised persons. Store in a dry, well ventilated place away from sources of heat, ignition and direct sunlight.

7.3 Specific end use(s)

No specific advice for end use available.

8. Exposure Controls/Personal Protection

8.1 Control parameters

Ingredients with Occupational Exposure Limits

(EU)

<u>Name</u>	CAS-No.	LTEL ppm	STEL ppm	STEL mg/m3	LTEL mg/m3
phenol, polymer with formaldehyde, glycidyl ether	28064-14-4				
Reaction product: bisphenol-A- (epichlorhydrin) epoxy resin (number average molecular weight <= 700)	25068-38-6				
Benzyl alcohol	100-51-6				
titanium dioxide	13463-67-7				
chromic oxide	1308-38-9				
Lead sulfochromate yellow	1344-37-2				
Dibutyl phthalate	84-74-2				
Solvent naphtha (petroleum), light arom.	64742-95-6				
Name	<u>CAS-No.</u>	OEL Note			
phenol, polymer with formaldehyde, glycidyl ether	28064-14-4				
Reaction product: bisphenol-A- (epichlorhydrin) epoxy resin (number average molecular weight <= 700)	25068-38-6				
Benzyl alcohol	100-51-6				
titanium dioxide	13463-67-7				
chromic oxide	1308-38-9				
Lead sulfochromate yellow	1344-37-2				
Dibutyl phthalate	84-74-2				
Solvent naphtha (petroleum), light arom.	64742-95-6				

FURTHER INFORMATION: Refer to the regulatory exposure limits for the workforce enforced in each country.

8.2 Exposure controls

Personal Protection

RESPIRATORY PROTECTION: No personal respiratory protective equipment normally required. Respirator with a vapor filter.

EYE PROTECTION: Safety glasses.

HAND PROTECTION: Impervious gloves. Take note of the information given by the producer concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact). Long sleeved clothing. Remove and wash contaminated clothing before re-use. Rubber or plastic apron.

OTHER PROTECTIVE EQUIPMENT: No Information

ENGINEERING CONTROLS: Avoid contact with skin, eyes and clothing. Ensure adequate ventilation, especially in confined areas.

9. Physical and Chemical Properties

9.1	Information on basic physical and chemical properties	
	Appearance:	Viscous Liquid
	Physical State	Liquid
	Odor	Ероху
	Odor threshold	Not determined
	рН	Not determined
	Melting point / freezing point (°C)	Not determined
	Boiling point/range (°C) Flash Point, (°C) Evaporation rate Flammability (solid, gas)	150 - N.D.
		101
		Slower than ether
		Not determined
	Upper/lower flammability or explosive limits	0.5 - 13
	Vapour Pressure	Not determined
	Vapour density	Heavier than air
	Relative density	1.32 - 1.38
	Solubility in / Miscibility with water	Not determined
	Partition coefficient: n-octanol/water	Not determined
	Auto-ignition temperature (°C)	Not determined
	Decomposition temperature (°C)	Not determined
	Viscosity	Not determined
	Explosive properties	Not determined
	Oxidising properties	Not determined
9.2	Other information	
	VOC Content g/l:	30
	Calculated grams of VOC per liter of coating product a	
	Specific Gravity (g/cm3)	1.348

10. Stability and Reactivity

10.1 Reactivity

No reactivity hazards known under normal storage and use conditions.

10.2 Chemical stability

No decomposition if stored and applied as directed. StableStable under normal conditions.

10.3 Possibility of hazardous reactions

Hazardous polymerisation does not occur.

10.4 Conditions to avoid

Extremes of temperature and direct sunlight.

10.5 Incompatible materials Strong oxidizing agents. Acids and bases. Amines.

10.6 Hazardous decomposition products

Thermal decomposition can lead to release of irritating gases and vapours. Alcohols. Exothermic reaction. Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), dense black smoke.

11. Toxicological Information

11.1 Information on toxicological effects

Acute Toxicity:	
Oral LD50:	No information
Inhalation LC50:	No information
Irritation:	No information available.
Corrosivity:	No information available.
Sensitization:	No information available.
Repeated dose toxicity:	No information available.
Carcinogenicity:	This product contains one or more carcinogenic substances. See hazard classification and precautionary statements in Section 2 for further information.
Mutagenicity:	No information available.
Toxicity for reproduction:	No information available.

If no information is available above under Acute Toxicity then the acute effects of this product have not been tested. Data on individual components are tabulated below:

CAS-No.	Chemical Name	Oral LD50	Dermal LD50	Vapor LC50
28064-14-4	phenol, polymer with formaldehyde, glycidyl ether	5000 mg/kg. oral, rat	>2000 mg/kg, rabbit	
25068-38-6	Reaction product: bisphenol-A- (epichlorhydrin) epoxy resin (number average molecular weight <= 700)	>2000 mg/kg, rat, oral	>2000 mg/kg, rat	
100-51-6	Benzyl alcohol	1230 mg/kg, rat	2000 mg/kg, rabbit	1000 ppm, rat
13463-67-7	titanium dioxide	10000 mg/m3, oral (rat)		
64742-95-6	Solvent naphtha (petroleum), light arom.	4700 mg/kg, oral, rat	>2000 mg/kg	3670 ppm/8 hours, rat, inhalation

Additional Information:

This product is classified as a "Reproductive Toxicity - Category 2" due to containing a substance classified as a reproductive toxin via ingestion / oral exposure route only. Normal product application methods by trained crew members would not present a risk of oral exposure or ingestion. This product may contain Titanium Dioxide, which is listed by IARC as possibly carcinogenic to humans (Group 2B). This listing is based on inadequate evidence of carcinogenicity in humans and sufficient evidence in experimental animals. This classification is relevant when exposed to titanium dioxide in dust or powder form only, including cured product that is subject to sanding, grinding, cutting, or other surface preparation activities.

12. Ecological Information

12.1	Toxici	ty:				
	EC	50 48hr (Daphnia):	No info	ormation		
	IC5	0 72hr (Algae):	No inf	ormation		
	LC	50 96hr (fish):	No inf	ormation		
12.2	Persis	tence and degradability:	No inf	ormation		
12.3	Bioac	cumulative potential:	No inf	ormation		
12.4	Mobili	ty in soil:	No inf	ormation		
12.5 Results of PBT and vPvB assessment:		The pr	oduct does not mee	et the criteria for PBT/VP	vB in accordance with Annex XIII.	
12.6	Other	adverse effects:	No inf	ormation		
CAS-	<u>-No.</u>	Chemical Name		<u>EC50 48hr</u>	<u>IC50 72hr</u>	<u>LC50 96hr</u>
2806	4-14-4	phenol, polymer with formaldehyde, ether	glycidyl	No information	No information	
2506	8-38-6	Reaction product: bisphenol-A- (epichlorhydrin) epoxy resin (number melanular unsight (= 700)	er average	No information	No information	

	molecular weight <= 700)			
100-51-6	Benzyl alcohol	230 mg/l	700 mg/l	460 mg/l
13463-67-7	titanium dioxide	>100 mg/l (EC50, 48h, Daphnia magna OECD202)ation	No information	>1000 mg/l
1308-38-9	chromic oxide	No information	No information	
1344-37-2	Lead sulfochromate yellow	No information	No information	
84-74-2	Dibutyl phthalate	No information	No information	
64742-95-6	Solvent naphtha (petroleum), light arom.	>1 - 10 mg/l	>1 - 10 mg/l	>10-100 mg/l

13. Disposal Considerations

13.1 WASTE TREATMENT METHODS: If recycling is not practicable, dispose of in compliance with local regulations. Dispose of wastes in an approved waste disposal facility. Empty containers should be taken to an approved waste handling site for recycling or disposal.

14.	Transport Information	
14.1	UN number	UN 3082
14.2	UN proper shipping name	Environmentally hazardous substance, Liuquid, N.O.S
	Technical name	Not applicable
14.3	Transport hazard class(es)	9
	Subsidiary shipping hazard	Not applicable
14.4	Packing group	PG III
14.5	Environmental hazards	Not applicable
14.6	Special precautions for user	Not applicable
	EmS-No.:	Not applicable
14.7	Transport in bulk according to Annex II of MARPOL 73/78 and the IBC code	Not applicable

Safety, health and environmental regulations/legislation for the substance or mixture:

National Regulations:						
Denmark Product Registration Number:	Not available					
Danish MAL Code:	Not available					
Danish MAL Code - Mixture:	Not available					
Sweden Product Registration Number:	Not available					
Norway Product Registration Number:	Not available					
WGK Class:	Not available					

15.2 Chemical Safety Assessment:

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

16. Other Information

Text for GHS Hazard Statements shown in Section 3 describing each ingredient:

	• •
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H350	May cause cancer.
H360	May damage fertility or the unborn child.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.

Reasons for revision

No Information

List of References:

This Safety Data Sheet was compiled with data and information from the following sources:

The Ariel Regulatory Database provided by the 3E Corporation in Copenhagen, Denmark; European Union Commission Regulation No. 1907/2006 on REACH as amended within Commission Regulation (EU) 2015/830; European Union (EC) Regulation No. 1272/2008 on the classification, labelling and packaging of substances and mixtures (CLP Regulation) and subsequent technical progress adaptations (ATP); EU Council Decision 2000/532/EC and its Annex entitled "List of Wastes".

Acronym & Abbreviation Key:

CLP	Classification, Labeling & Packaging Regulation
EC	European Commission
EU	European Union
US	United States
CAS	Chemical Abstract Service
EINECS	European Inventory of Existing Chemical Substances
REACH	Registration, Evaluation, Authorization of Chemicals Regulation
GHS	Globally Harmonized System of Classification and Labeling of Chemicals
LTEL	Long term exposure limit
STEL	Short term exposure limit

Date Printed: 29/03/2018

OEL	Occupational exposure limit
mqq	Parts per million
mg/m3	Milligrams per cubic meter
TLV	Threshold Limit Value
ACGIH	American Conference of Governmental Industrial Hygienists
OSHA	Occupational Safety & Health Administration
PEL	Permissible Exposure Limits
VOC	Volatile organic compounds
q/1	Grams per liter
mg/kg	Milligrams per kilogram
N/A	Not applicable
LD50	Lethal dose at 50%
LC50	Lethal concentration at 50%
EC50	Half maximal effective concentration
IC50	Half maximal inhibitory concentration
PBT	Persistent bioaccumulative toxic chemical
vPvB	Very persistent and very bioaccumulative
EEC	European Economic Community
ADR	International Transport of Dangerous Goods by Road
RID	International Transport of Dangerous Goods by Rail
UN	United Nations
IMDG	International Maritime Dangerous Goods Code
ΙΑΤΑ	International Air Transport Association
MARPOL	International Convention for the Prevention of Pollution From Ships, 1973 as
modified by the Pr	
IBC	International Bulk Container
RTI	Respiratory Tract Irritation
NE	Narcotic Effects

For further information, please contact: Technical Services Department

The information on this sheet corresponds to our present knowledge. It is not a specification and it does not guarantee specific properties. The information is intended to provide general guidance as to health and safety based upon our knowledge of the handling, storage, and use of the product. It is not applicable to unusual or non-standard uses of the product or where instructions and recommendations are not followed.